

EMB8-70-M

EMB II SERIES

8" DOWN-FIRING MARINE 70V SUBWOOFER



Size	9.75 w x 9.75 d x 11.25 h (in) 248 w x 248 d x 286 h (mm)
Freq Response	28-150Hz \pm 3dB
Impedance	70 volt
Sensitivity	89dB 2.83V/1m
Voltage	70
70 Volt Power	100W Toroidal Transformer
Woofers	(1) 6.5" (165mm) Active (1) 8" (203mm) Passive
Enclosure	Aluminum
Finish	Satin Black

(1) 6.5" (165mm) Internal Aluminum Active Woofer (1) 8" (203mm) Aluminum Passive Radiator

One of many available options in the EMB II Subwoofer series features a very contemporary, non-obtrusive cabinet design. The down-firing design provides 4 finished sides for flexibility in room placement. Built from solid aircraft grade aluminum and expertly finished to your color preference, the craftsmanship of this compact subwoofer exudes luxury and performance.

The EMB8-70-M is an outdoor/marine rated down-firing subwoofer. Internally, the EMB8-70-M utilizes our famous "Energy Multiplying Bandpass" technology to obtain high output and low distortion from a very compact enclosure. Inside, the cabinet features a patented 6.5" woofer and a pneumatically phase coupled 8" passive radiator, both with aluminum cones and rubber surrounds. The EMB8-70-M subwoofer has been tuned to perform all the way down to an impressive 28 Hz!

Being a 70V subwoofer, the EMB8-70-M can be used in any 70V installation where long speaker lines are required. The standard 70V transformer is 100W.

The EMB8-70-M can be ordered in any of our standard outdoor colors, additional lead times may apply.

An 8-ohm outdoor/marine version is also available as a EMB8-8-M.



2185 Park Place, Minden, NV 89423
Ph: 775.461.7500
www.jamesloudspeaker.com

POWERFUL REPRODUCTION

20220111